

Boundary Layer Ingestion

Benefit Quantification and Analysis Framework

Alejandra Uranga

Gabilan Assistant Professor

Aerospace & Mechanical Engineering




USC University of
Southern California

6th International Workshop on Aviation and Climate Change
University of Toronto Institute for Aerospace Studies
May 16–18, 2018

Outline

- 1 Introduction
- 2 D8 Aircraft: Conceptual Studies
- 3 Experimental Measurement of BLI Benefit
- 4 Analysis Framework: “Data Mining”
- 5 Other BLI-Related Topics

Boundary Layer Ingestion (BLI)



- ▶ BLI reduces wasted KE in combined jet+wake (mixing losses)
 - ▶ Long known to have large potential, never realized for aircraft
 - ▶ Ambiguous decomposition into drag and thrust
(airframe) (propulsion system)
- ⇒ use of **power balance** instead of force accounting

Summary

- ▶ Closer integration of propulsion system and airframe provides new opportunities to reduce fuel burn and emissions of commercial aircraft
 - ▶ Boundary layer ingestion (BLI)
 - ▶ Novel configurations
 - ▶ System optimization (airframe, engine, operations)
- ▶ Flow power and dissipation in power balance framework provide useful metrics for integrated configurations
- ▶ D8 wind tunnel tests
 - ▶ Quantification of aerodynamic BLI benefit
 - ▶ Proof-of-concept for use of BLI in transport aircraft
- ▶ Aerodynamic framework developed to analyze aircraft with BLI

Major Collaborators

MIT

Mark Drela
Edward Greitzer

UTRC

Scott Ochs
Greg Tillman

Pratt & Whitney

Wes Lord (retired)

University of Michigan

Joaquim Martins

NASA

Scott Anders (LaRC)
Greg Gatlin (LaRC)
Judith Hannon (LaRC)
James Heidmann (GRC)
Natari Madavan (ARC)
Shishir Pandya (ARC)
Sally Viken (LaRC)



United Technologies
Research Center



Pratt & Whitney
A United Technologies Company




Outline

- 1 Introduction
- 2 D8 Aircraft: Conceptual Studies
- 3 Experimental Measurement of BLI Benefit
- 4 Analysis Framework: “Data Mining”
- 5 Other BLI-Related Topics

Phase 1: D8 Aircraft Concept

2008-2010




- ▶ B737-800/A320 class
- ▶ 180 PAX, 3,000 nm range
- ▶ Double-bubble lifting fuselage with pi-tail
- ▶ Two aft, flush-mounted engines ingest $\sim 40\%$ of fuselage BL
- ▶ Cruise Mach 0.72
- 37% fuel with current tech (configuration)
- 66% fuel with advanced tech (2025-2035)

No “magic bullet”

E. Greitzer et al. 2010, NASA CR 2010-216794

A. Uranga et al. 2014, AIAA 2014-0906

NASA-MIT Cooperative Agreement NNX08AW63A



Photos NASA/George Homich

System Impact of BLI

BLI benefits

- ▶ *Aerodynamic* (direct) benefits
 - ▶ Reduced jet and wake dissipation
 - ▶ Reduced nacelle wetted area
- ▶ *System-level* (secondary) benefits
 - ▶ Reduced engine weight
 - ▶ Reduced nacelle weight
 - ▶ Reduced vertical tail size
 - ▶ Compounding from reduced overall weight


“Morphing” sequence: B737-800 \mapsto D8

- ▶ Features of D8 introduced one at a time
- ▶ Sequence of conceptual designs, optimized at each step (TASOPT)

E. Greitzer et al. 2010, NASA CR 2010-216794

M. Drela 2011, AIAA 2011-3970

Morphing Sequence: B737-800 \mapsto D8.2 \mapsto D8.6



Phase 3: Trade-Offs Summary

2015-2017

Metric: Payload-Range Fuel Consumption =
$$\frac{\text{Fuel Energy Consumed}}{\text{Payload Weight} \times \text{Range}}$$

- ▶ **D8 configuration benefit** (20 ± 3)%
relative to tube-and-wing at same cruise speed and technology
- ▶ **N+3 technology benefit** (45 ± 2)% relative to 1990s tech
 - ▶ Tech advances benefit tube-and-wing more:
D8 has lower structural/total weight and higher payload/total weight
- ▶ **Slowing down from Mach 0.78 to 0.72** (5 ± 1.5)%
 - ▶ Tube-and-wing benefits more from lower speed

Outline

- 1 Introduction
- 2 D8 Aircraft: Conceptual Studies
- 3 Experimental Measurement of BLI Benefit**
- 4 Analysis Framework: “Data Mining”
- 5 Other BLI-Related Topics


Phase 2: Airframe-Engine Integration

2010-2015


Quantification of D8 BLI benefit (experimental/computational)

- ▶ Direct back-to-back comparison of BLI vs non-BLI
- ▶ Wind tunnel tests of 1:11 scale (4 m span) powered models

Non-BLI
(Podded)



BLI
(Integrated)



BLI Benefit

BLI benefit (aerodynamic)

Savings in power required for given net stream-wise force with BLI engines relative to non-BLI engines

Power metric

Mechanical flow power transmitted to the flow by the propulsors



$$P_K = \oint (p_o - p_{o\infty}) \mathbf{V} \cdot \hat{n} dS \quad (\text{incompressible})$$

$$\text{BLI benefit} \equiv \left. \frac{P_{K_{\text{non-BLI}}} - P_{K_{\text{BLI}}}}{P_{K_{\text{non-BLI}}}} \right|_{\text{at given } F_X}$$

Obtaining P_K

Method 1: Integration of the flow on propulsor stream-tube


$$P_K = \int_{\text{exit}} (p_o - p_{o\infty}) \mathbf{V} \cdot \hat{n} dS - \int_{\text{inlet}} (p_o - p_{o\infty}) \mathbf{V} \cdot \hat{n} dS$$



Method 2: Conversion of *electrical* power provided to the propulsor motors

$$\underbrace{P_K}_{\text{mechanical flow power}} = \underbrace{\eta_f}_{\substack{\text{fan} \\ \text{efficiency} \\ P_K/P_S}} \times \underbrace{\eta_m}_{\substack{\text{motor} \\ \text{efficiency} \\ P_S/P_E}} \times \underbrace{P_E}_{\text{electrical power}}$$

Phase 2: Demonstrated Aerodynamic BLI Benefit 2010-2015



NASA-MIT Cooperative Agreement NNX11AB35A

Outline

- 1 Introduction
- 2 D8 Aircraft: Conceptual Studies
- 3 Experimental Measurement of BLI Benefit
- 4 Analysis Framework: “Data Mining”**
- 5 Other BLI-Related Topics

BLI Benefit Sources

- 1 Lower propulsor **jet dissipation** and higher **propulsive efficiency**: more useful power put into the flow
- 2 Lower **surface dissipation** (smaller nacelle size and surface velocities)
- 3 Lower **wake dissipation** (partial elimination of viscous wake)
- 4 Lower **weight** due to smaller nacelles and smaller engines, which in turn enables smaller wings, and thus even less weight

1 + 2 + 3 = **aerodynamic benefit**: less flight power required for a given airframe operating at the same lift coefficient

4 = **system-level benefit** after aircraft re-optimizations


Power Balance Method

Consider mechanical energy sources and sinks:


$$[\text{Net Force}] = [\text{Dissipation}] - [\text{Power In}]$$

$$\underbrace{F_X}_{\text{"drag - thrust"}} V_\infty = (\Phi_{\text{surf}} + \Phi_{\text{wake}} + \Phi_{\text{vortex}} + \Phi_{\text{jet}}) - (\underbrace{P_K}_{\text{mechanical flow power}} + \underbrace{\cancel{P_V}}_{p \, dV \text{ power}})$$

Non-BLI Configuration



BLI Configuration



M. Drela 2009, AIAA Journal 47(7)

Airframe Dissipation (1/2)

- Conventional drag decomposition:

$$D' V_\infty = \underbrace{\Phi'_{\text{surf}} + \Phi'_{\text{wake}}}_{D'_p V_\infty \text{ (profile)}} + \underbrace{\Phi'_{\text{vortex}}}_{D'_i V_\infty \text{ (induced)}}$$

- Surface dissipation: $\Phi'_{\text{surf}} = (1 - f_{\text{wake}}) D'_p V_\infty$

$$\Phi_{\text{surf}} = (1 - f_{\text{wake}}) D'_p V_\infty - \Delta\Phi_{\text{surf}}$$

$$\text{where } f_{\text{wake}} \equiv \frac{\Phi'_{\text{wake}}}{\Phi'_{\text{surf}} + \Phi'_{\text{wake}}}$$

$$\Delta\Phi_{\text{surf}} \equiv \Phi'_{\text{surf}} - \Phi_{\text{surf}} > 0$$

Airframe Dissipation (2/2)

- ▶ Wake dissipation:

$$\Phi'_{\text{wake}} = f_{\text{wake}} (\Phi'_{\text{surf}} + \Phi'_{\text{wake}}) = f_{\text{wake}} D'_p V_{\infty}$$

$$\Phi_{\text{wake}} = (1 - f_{\text{BLI}}) \Phi'_{\text{wake}} = (1 - f_{\text{BLI}}) f_{\text{wake}} D'_p V_{\infty}$$

where $f_{\text{BLI}} \equiv$ boundary layer **ingestion fraction**

= fraction of total airframe viscous kinetic energy defect
ingested by propulsors

- ▶ Vortex dissipation: $\Phi_{\text{vortex}} = \Phi'_{\text{vortex}} = D'_i V_{\infty}$

assuming comparison is made with same airframe at fixed C_L

Jet Dissipation

- ▶ Jet dissipation (with or without BLI):

$$\begin{aligned}\Phi_{\text{jet}} &= \iint_{\text{exit}} \frac{1}{2} (V - V_{\infty})^2 \, d\dot{m} \\ &= \frac{1}{2} (V_{\text{jet}} - V_{\infty})^2 \dot{m}\end{aligned}$$

for $\dot{m} = N_{\text{prop}} \rho_{\text{jet}} V_{\text{jet}} A_{\text{jet}}$ (total propulsor mass flow)

and assuming uniform velocity V_{jet} across the jet
(jet p_t non-uniformity \ll propulsor p_t rise)

Mechanical Flow Power

$$\begin{aligned} P_K &\equiv \oiint_{\text{prop}} \left[p_\infty - p + \frac{1}{2} \rho (V_\infty^2 - V^2) \right] \mathbf{v} \cdot \hat{\mathbf{n}} \, dS \\ &= \underbrace{\frac{1}{2} (V_{\text{jet}}^2 - V_\infty^2) \dot{m}}_{(\text{exit})} - \underbrace{(-f_{\text{BLI}} \Phi'_{\text{surf}})}_{(\text{inlet})} \\ &= \frac{1}{2} (V_{\text{jet}}^2 - V_\infty^2) \dot{m} + \underbrace{(1 - f_{\text{wake}}) f_{\text{BLI}} D'_p V_\infty}_{\text{extra power}} \end{aligned}$$

Parametric Expressions

Parametric expression for **power required** and **stream-wise force** in terms of reference non-BLI configuration and propulsor operation

$$C_{P_K} = N_{\text{prop}} \left[\left(\frac{V_{\text{jet}}}{V_{\infty}} \right)^2 - 1 \right] \frac{\rho_{\text{jet}}}{\rho_{\infty}} \frac{V_{\text{jet}}}{V_{\infty}} \frac{A_{\text{jet}}}{A_{\text{noz}}} \frac{A_{\text{noz}}}{S_{\text{ref}}} + (1 - f_{\text{wake}}) f_{\text{BLI}} C'_{D_p}$$

$$C_X = C'_D - f_{\text{BLI}} C'_{D_p} - \Delta C_{\Phi_{\text{surf}}} - 2N_{\text{prop}} \left(\frac{V_{\text{jet}}}{V_{\infty}} - 1 \right) \frac{\rho_{\text{jet}}}{\rho_{\infty}} \frac{V_{\text{jet}}}{V_{\infty}} \frac{A_{\text{jet}}}{A_{\text{noz}}} \frac{A_{\text{noz}}}{S_{\text{ref}}}$$


- ▶ Valid with and without BLI, depending on value of f_{BLI}
- ▶ Jet properties (ρ_{jet} , A_{jet} , V_{jet}) with and without BLI may differ
- ▶ Quantify BLI benefit relative to known non-BLI configuration

Major Design Parameters for BLI Aircraft

- (i) **Ingested dissipation** $f_{\text{BLI}} C'_{D_p}$
- (ii) How “well-designed” the BLI engine **installation** is $\Rightarrow \Delta\Phi_{\text{surf}}$
- (iii) **Propulsor operating points** for each of the configurations
 \Rightarrow respective propulsor jet velocities or mass flows

Data Mining: Application to D8 Wind Tunnel Tests

Use expressions for C_{P_K} and C_X to fit experimental data ($C_L = C'_L = 0.64$)



$$C'_D = 0.0370$$

$$\Delta C_{\Phi_{\text{surf}}} = 0.0012$$

$$f_{\text{wake}} = 0.080$$



$$\frac{A_{\text{jet}}}{A_{\text{noz}}} = 0.955$$

$$C_{X_0} = 0.0357$$


$$C_{D_{\text{airframe}}} = 0.0338$$

Propulsive Efficiency


$$\eta_p \equiv \frac{P_K - \Phi_{\text{jet}}}{P_K}$$




Variable Nozzle Area: Different Propulsor Designs




Bases for Comparison



Bases for Comparison



Bases for Comparison




Outline

- 1 Introduction
- 2 D8 Aircraft: Conceptual Studies
- 3 Experimental Measurement of BLI Benefit
- 4 Analysis Framework: “Data Mining”
- 5 Other BLI-Related Topics**


High-Efficiency, High-OPR, Small Cores (N+3 Phase 2, P&W)

Pratt & Whitney – Lord et al., AIAA 2015-0071 : reverse core engine arch.




D8 Transonic Design (N+3 Phase 3, U.Michigan)

Transonic wing and engine integration MDO for $Mach = 0.72, 0.78$:
aero-structural optimization with loosely coupled engine model




Airframe-Propulsion Integration Challenges

Integration lines strongly dependent on optimization's objective function



- ▶ Hard to identify MDO objective: need fully coupled engine model
- ▶ High sensitivity of fan face condition to diffuser shape

Airframe-Propulsion Integration Challenges



References

- Drela, M., “Power Balance in Aerodynamic Flows”, *AIAA Journal*, Vol. 47, No. 7, 2009, pp. 1761–1771. doi:10.2514/1.42409 **[power balance method]**
- Uranga, A., Drela, M., Greitzer, E., Titchener, N., Lieu, M., Siu, N., Huang, A., Gatlin, G., and Hannon, J., “Preliminary Experimental Assessment of the Boundary Layer Ingestion Benefit for the D8 Aircraft”, AIAA-2014-0906, *52nd AIAA Aerospace Sciences Meeting, SciTech 2014*, National Harbor, Maryland, 13–17 Jan. 2014. doi:10.2514/6.2014-0906 **[preliminary wind tunnel test results, morphing chart]**
- Uranga, A., Drela, M., Greitzer, E. M., Hall, D. K., Titchener, N. A., Lieu, M. K., Siu, N. M., Casses, C., Huang, A. C., Gatlin, G. M., and Hannon, J. A., “Boundary Layer Ingestion Benefit of the D8 Transport Aircraft”, *AIAA Journal*, Vol. 55, No. 11, pp. 3693–3708, 2017. doi:10.2514/1.J055755 **[wind tunnel tests]**
- Uranga, A., Drela, M., Hall, D. K., and Greitzer, E. M., “Analysis of the Aerodynamic Benefit from Boundary Layer Ingestion for Transport Aircraft”, *AIAA Journal*, in press **[analysis, “data mining”]**
- Hall, D. K., Huang, A. C., Uranga, A., Greitzer, E. M., Drela, M., and Sato, S., “Boundary Layer Ingestion Propulsion Benefit for Transport Aircraft”, *Journal of Propulsion and Power*, Vol. 33, No. 5, pp. 1118–1129, 2017. doi:10.2514/1.B36321 **[analysis]**

Contact

Alejandra Uranga, Ph.D.

Gabilan Assistant Professor

Aerospace & Mechanical Engineering Dept.

University of Southern California

Email: auranga@usc.edu

Phone: (213) 821 - 0846

Web: uranga.usc.edu